

4. COOKING APPLIANCES

AGA LTD

Station Road, Ketley, Telford, Shropshire TF1 5AQ www.aga-web.co.uk Tel: 0845 762 6147

Product Name	Manufacturers Declared efficiency	Provides C H DHW	Dimensions (mm)			Cooker Input kW	Boiler Output kW	Burner Types	Fuel C2/D	SER Access	Flue Option	OFCERT License No	
			H	W	D								
AGA OC		C	851	987	679	2.6-4.3		1 x Vap	C2	F S T	100mm	CF	0500090116
AGA OCB 90		C H DHW	851	987	679	3.0-4.9	1.09	1 x Vap	C2	F S T	100mm	CF	0500090117
AGA OCB 135		C H DHW	851	981	679	3.7-4.9	1.6	1 x Vap	C2	F S T	100mm	CF	0500090118
AGA OE		C	851	1487	679	2.7-4.3		1 x Vap	C2	F S T	100mm	CF	0500090119
AGA OEB		C DHW	851	1487	679	3.7-4.9	1.09	1 x Vap	C2	F S T	100mm	CF	0500090120
Rayburn 300K		C	820	840	542	2.2-5.5		1 x Vap	C2	F S T	100mm	CF	400040013
Rayburn 308K		C DHW	820	840	542	2.8-7.4	2.35	1 x Vap	C2	F S T	100mm	CF	400040014
Rayburn 400K		C	910	905	542	14.6		PJ	C2	F T	127mm	CF	0400010522
Rayburn 400K (Powerflue)		C	910	905	542	14.6		1 x PJ	C2		54mm	PF	0400010523
Rayburn 440K	84.7% *	C H DHW	910	905	542	14.2	12	2 x PJ	C2		125mm	BF	0400010524
Rayburn 460K	84.8% *	C H DHW	910	905	542	17.6	17.6	2 x PJ	C2	F T	127mm	CF	0400020007
Rayburn 480K	85.0% *	C H DHW	910	905	542	17.6	23.4	2 x PJ	C2	F T	127mm	CF	0400020008
Rayburn 499K	84.6% *	C H DHW	910	905	542	17.6	29.3	2 x PJ	C2	F T	127mm	CF	0400020009
Rayburn 600K		C	910	995	542	17.6		1 x PJ	C2	F	127mm	CF	
Rayburn 660K	85%	C H DHW	910	995	542	17.6	17.5	2 x PJ	C2	F	127mm	CF	
Rayburn 680K	84.90%	C H DHW	910	995	542	17.6	23.5	2 x PJ	C2	F	127mm	CF	
Rayburn 699K	84.40%	C H DHW	910	995	542	17.6	29.3	2 x PJ	C2	F	127mm	CF	
Rayburn 880K	85.70%	C H DHW	920	1070	650	15	24.3	2 x PJ	C2	F	127mm	CF	
Rayburn 8120K	85.60%	C H DHW	920	1070	650	15	37	2 x PJ	C2	F	127mm	CF	
Rayburn 8150K	85.30%	C H DHW	920	1070	650	15	43.8	2 x PJ	C2	F	127mm	CF	
Rayburn 440KB		C H DHW	910	905	542	14.2	12	2 x PJ	C2			BF	0400010524
Rayburn 460KB		C H DHW	910	905	542	17.6	17.6	2 x PJ	C2	F T		BF	0400020010
Rayburn 480KB		C H DHW	910	905	542	17.6	23.4	2 x PJ	C2	F T		BF	0400020011
Rayburn 499KB		C H DHW	910	905	542	17.6	29.3	2 x PJ	C2	F T		BF	0400020012
Rayburn Cookmaster XT Oil (KP/F)		C H DHW	910	905	620	14.6		1 x PJ	C2		54mm	PF	0400090501

4. COOKING APPLIANCES

REDFYRE COOKERS LTD

Osprey Road, Sowton Industrial Estate, Exeter, Devon EX2 7JG redfyre@gazco.com Tel: 01392 444070 Fax: 01392 444804

Product Name	Manufacturers Declared efficiency	Provides C H DHW	Dimensions (mm)			Cooker Input kW	Boiler Output kW	Burner Types	Fuel C2/D	SER Access	Flue Option	OFCERT License No
			H	W	D							
Redfyre Classic		C H DHW	880	990	548	6.37	13.4		C2	F T	125mm	CF
Redfyre Classic		C DHW	880	990	549	2.55-6.37	10	1 x Vap	C2	F T		CF
Redfyre Traditional 4 Oven		C	880	990	550	5 max	6.8	1 x Vap	C2	F T		CF
Redfyre Traditional 2 Oven		C	920	920	630	5 max	15.6	1 x Vap	C2	F T		CF
Redfyre Central Heating 60K		C DHW	920	920	630	17	15.6	2 x PJ	C2	F T		CF
Redfyre Central Heating 100K		C H DHW	920	920	630	17	19.6-4.4	2 x PJ	C2	F T		CF
Redfyre Central Heating 80K		C H DHW	920	889	568	17	16.6-4.4	2 x PJ	C2	F T		CF
Redfyre Central Heating 120K		C H DHW	915	920	530	17	20.2	2 x PJ	C2	F T		CF

SNUGHOME COOKERS LTD

Unit 18C Penley Business Park, Penley, Wrexham LL13 0LQ www.snughomecookers.co.uk barry@snughomecookers.co.uk Sales Tel: 07860 676793 Technical Tel: 07595 862703

Product Name	Manufacturers Declared efficiency	Provides C H DHW	Dimensions (mm)			Cooker Input kW	Boiler Output kW	Burner Types	Fuel C2/D	SER Access	Flue Option	OFCERT License No
			H	W	D							
M - C - TS												
AGA OC		C			Conversion	9.4 - 4.7 - 1.5		PJ	C2/D/B	F S T	CF	PF
AGA OCB		C H DHW			Conversion	9.4 - 4.7 - N/A		PJ	C2/D/B	F S T	CF	PF
AGA GC		C			Conversion	9.4 - 4.7 - 1.5		PJ	C2/D/B	F S T	CF	PF
AGA GCB		C H DHW			Conversion	9.4 - 4.7 - N/A		PJ	C2/D/B	F S T	CF	PF
AGA OE		C			Conversion	9.4 - 4.7 - N/A		PJ	C2/D/B	F S T	CF	PF
AGA OEB		C H DHW			Conversion	9.4 - 4.7 - N/A		PJ	C2/D/B	F S T	CF	PF
AGA GE		C			Conversion	9.4 - 4.7 - N/A		PJ	C2/D/B	F S T	CF	PF
AGA GEB		C H DHW			Conversion	9.4 - 4.7 - N/A		PJ	C2/D/B	F S T	CF	PF
AGA Deluxe		C			Conversion	9.4 - 4.7 - 1.5		PJ	C2/D/B	F S T	CF	PF
Nobel 2 Oven Twyford Model		C			Conversion	9.4 - 4.7 - 1.7		PJ	C2/D/B	F S T	CF	PF
Rayburn OF22	87.5% (When firing)	C H DHW			Conversion	14.7		PJ	C2/D/B	F S T	CF	PF
Rayburn G33	87.5% (When firing)	C H DHW			Conversion	15.6		PJ	C2/D/B	F S T	CF	PF
Rayburn OF7	88% (When firing)	C			Conversion	9.4 (Firing)		PJ	C2/D/B	F S T	CF	PF
Rayburn OF7	88% (When firing)	C H DHW			Conversion	9.4 (Firing)		PJ	C2/D/B	F S T	CF	PF
Rayburn G7	87.5% (When firing)	C			Conversion	9.4 (Firing)		PJ	C2/D/B	F S T	CF	PF
Rayburn G7	87.5% (When firing)	C H DHW			Conversion	9.4 (Firing)		PJ	C2/D/B	F S T	CF	PF
Rayburn 200 - 209	87.5% (When firing)	C			Conversion	9.4 (Firing)		PJ	C2/D/B	F S T	CF	PF
Rayburn 200-209	87.5% (When firing)	C H DHW			Conversion	9.4 (Firing)		PJ	C2/D/B	F S T	CF	PF

4. COOKING APPLIANCES

WATERFORD STANLEY

Bilberry, Waterford, Ireland www.waterfordstanley.com Tel: 00353 513 02375 Fax: 00353 513 02399

Product Name	Manufacturers Declared efficiency	Provides			Dimensions (mm)			Cooker Input kW	Boiler Output kW	Burner Types	Fuel C2/D	SER Access	Flue Option	OFCERT License No
		C	H	DHW	H	W	D							
Traditional Oil 20k		C	H	DHW	880	990	548	13.4	5.9	1 x Vap	C2	F S T	125mm	CF
Traditional Oil DHW		C		DHW	880	990	549	10	3.6	1 x Vap	C2	F S T	125mm	CF
Traditional Oil N/B		C			880	990	550	6.8		1 x Vap	C2	F S T	125mm	CF
TS 2 Dry Oil		C			920	920	630	15.6		1 x PJ	C2/D	F T	150mm	CF
TS2 DHW Oil		C		DHW	920	920	630	15.6	2.8	1 x PJ	C2/D	F T	150mm	CF
TS2 80k Oil		C	H	DHW	920	920	630	19.6-4.4	23.4	2 x PJ	C2/D	F T	150mm	CF
TS2 100k Oil		C	H	DHW	920	920	630	19.6-4.4	29.3	2 x PJ	C2/D	F T	150mm	CF
S90 Oil		C	H	DHW	920	889	568	20.2	13.7	1 x PJ	C2/D	F T	150mm	CF
Star Oil 60k		C	H	DHW	915	920	530	22	19.4	1 x PJ	C2/D	F T	150mm	CF